



## CHAIR SEAT

### STUFF

3 balls in White of Lehigh Mason Twine, 9oz/257g balls,  
each approx 76.6yd/70m (nylon)  
One pair size 10 (6mm) needles OR SIZE TO GET THE GAUGE

Stitch markers

Chair

Shown on page 23.

### THE MEASUREMENTS

15" (front) x 14" (deep) x 11" (back)/38cm x 35.5cm x 28cm

### THE GAUGE

14 sts and 22 rows to 4"/10cm over St st using size 10 (6mm) needles.  
BE SURE TO GET THE GAUGE.

### THE NOTE

- 1) This project is based on a chair whose seat frame measures 15"/38cm across the front, 11"/28cm across the back, and 14"/35.5cm from the front of the seat to the back. Adjust pattern appropriately to fit your chair.
- 2) Before beginning project, read through assemblage directions and make sure your chair can be well-protected from water damage.

### THE STITCH

**S2KP** Sl 2 sts, k1, pass 2 slipped sts over k1 (2 sts dec'd)

### MAKE THE CHAIR SEAT

chair seat top

■ Cast on 43 sts.

Work in garter st for 2 rows, then begin chart pat as foll: *Row 1 (RS)* Work first st, then work 14-st rep twice, work last 14 sts once more. Cont as established until 8 rows have been worked from beg. *Row 9* Cast on 4 sts and work these sts in St st, place marker (pm), work to end.

*Row 10* Cast on 4 sts and work these sts in St st, pm, work to end.

*Inc row K* to 1 st before first marker, yo, k1, slip marker (sl m), work to next marker, sl m, k1, yo, k to end.

Rep inc row every 6th row 6 times more—65 sts.

Work even in pats as established until piece measures 14"/35.5cm from beg. Bind off 4 sts at beg of next 2 rows—57 sts.

Work even for 4 more rows. Mark last row with stitch marker.

chair seat bottom

■ *Next (dec) row K* to 2 sts before first marker, ssk, sl m, knit to next marker, sl m, k2tog, k to end.

Working even in St st, work dec row every 6th row 6 times more. Work even in St st until last row meets cast-on edge when wrapped around chair seat. Bind off.

### ATTACH THE CHAIR SEAT

■ Lay the chair seat over the front seat support with RS up. Turn the chair upside down. Pull the seat around the back support and seam the bound-off edge to the cast-on edge. Set chair upright and seam side edges together around side supports.

■ To shrink and draw up fabric into a firm chair seat, set chair in tub or sink and pour very hot (boiling) water over the seat and allow to dry thoroughly. Make sure to carefully wrap the legs and stretchers between legs in plastic garbage bags to prevent water damage. 🌡️

### stitch key

■ k on rs, p on ws

✕ k2tog

✂ ssk

○ yo

▲ s2kp

